

## TC1037

- High performance low frequency transducer
- Ideal for installation due to steel housing and threaded guide
- Optional cable termination TL8038

The TC1037 is a rugged directional transducer with low frequency. It is specifically designed for underwater telephone systems. Can be used as a building block in special long range sonars or in sub bottom penetration single or multibeam systems.


### TECHNICAL SPECIFICATIONS

Usable frequency band:	6kHz to 15kHz
Transmitting sensitivity:	148dB ±3dB at 7,3kHz (re µPa/V at 1m)
Receiving sensitivity:	-168dB ±3dB at 7,3kHz (re 1V/µPa)
Impedance:	550ohm ±200ohm at 7,3kHz
Beam shape:	Conical
Beam width:	80°at 8kHz
Max input power:	400W (1% duty cycle)
Operating depth:	600m
Survival depth:	800m
Operating temperature range:	-2°C to +35°C
Storage temperature range:	-40°C to +70°C
Cable (Optional)	Connector and 9m cable, pigtail
Housing:	Special formulated NBR
Weight (air) incl. cable:	5,8kg


Please note that this product requires a minimum quantity per order




Horizontal Directivity Pattern




Receiving Sensitivity [dB re 1V/μPa @ 1m]




Transmitting Sensitivity [dB re 1μPa/V @ 1m]



Impedance



### Outline Dimensions



For information on export control regulations on this product, please refer to [www.reson.com](http://www.reson.com)



RESON reserves the right to change specifications without notice. © 2006 RESON A/S  
For Acoustical Measurement Accuracy please refer to [www.reson.com](http://www.reson.com) or contact sales.

**RESON A/S**  
Denmark  
Tel: +45 4738 0022  
E-mail: [reson@reson.dk](mailto:reson@reson.dk)

**RESON GmbH**  
Germany  
Tel: +49 431 720 7180  
E-mail: [reson@reson-gmbh.de](mailto:reson@reson-gmbh.de)

**RESON Inc.**  
USA  
Tel: +1 805 964-6260  
E-mail: [sales@reson.com](mailto:sales@reson.com)

**RESON B.V.**  
The Netherlands  
Tel: +31 (0)10 245 1500  
E-mail: [info@reson.nl](mailto:info@reson.nl)

**RESON Offshore Ltd.**  
United Kingdom  
Tel: +44 1224 709 900  
E-mail: [sales@reson.co.uk](mailto:sales@reson.co.uk)

**RESON Mediterranean SRL**  
Italy  
Tel: +39-051-572-643  
E-mail: [info@reson.it](mailto:info@reson.it)